

Product Overview

The **27-245** is a camera retention interface for selected Hyundai and Kia vehicles with a factory-fitted reverse camera and **24-pin camera connector**.

Please Note

- The purple wire is to be connected to 12v ignition feed

Common locations:

- Behind radio

Tools Required

- Trim panel removal tools
- Screwdriver or socket set
- Multimeter
- Suitable crimp connectors or soldering iron
- Insulation tape



Installation Steps

1. switch off the ignition for the vehicle and remove the key
2. Remove the radio to access the factory wiring behind the dashboard
3. Connect the large white plug on the 27-245 to the matching factory vehicle plug.
4. Connect the purple wire to a 12V ignition feed
5. Connect the black Ground wire to the vehicle chassis ground or a confirmed ground wire
6. Connect the yellow camera plug to the camera input on the aftermarket head unit.
7. Make sure all plugs are fully seated and secure
8. Secure the wiring, making sure it is not trapped, stretched, or near moving parts.
9. Fit the aftermarket head-unit and any removed trim.

Testing

- Turn the ignition on
- Check the camera works when in reverse gear with the ignition on
- Check image is clear and color is accurate
- If no image appears, check all connections

Need Technical Support?

Message our team on Whatsapp: 07770 814 793

Send your questions and photos so we can help you as quickly as possible.



Chat on WhatsApp