

Product Overview

The 27-260 is a camera input adapter for Toyota vehicles with the original Toyota Touch 2 system and a 28-pin camera connector. It allows an aftermarket rear-view camera to be added to the factory Toyota screen.

Please Note

Use an NTSC camera. Connect the Parking wire to the vehicle parking brake signal.



Common locations:

- Behind radio / display

Tools Required

- Trim panel removal tools
- Screwdriver or socket set
- Cable ties / loom tape
- Torch/ work light

Installation Steps

1. Switch off the ignition and remove the key.
2. Remove the radio/display to access the factory 28-pin connector.
3. Plug the 27-260 adapter into the matching 28-pin camera connector.
4. Connect the yellow RCA video input from the adapter to the aftermarket reverse camera.
5. Connect the camera power wire to a suitable 12V supply.
6. Connect the camera ground wire to a suitable ground.
7. Connect the dark green Parking wire to the vehicle parking brake signal.
8. Secure the adapter and wiring, making sure the cables are not trapped, stretched, or near moving parts.
9. Refit the radio/display and any removed trim.

Testing

- Switch on the ignition
- Ensure camera works when in reverse gear and is clear and stable
- If no image appears, check 28-pin connector and all other wire connections

Need Technical Support?

Message our team on Whatsapp: 07770 814 793

Send your questions and photos so we can help you as quickly as possible.



Chat on WhatsApp